



#### TECHNICAL SPECIFICATION:

MODEL NO. NT-250 / MODEL NO. NT-200

#### CHEESE PIPE DATA:

ID : 35 MM

OD : 40 MM

LENGTH : 220 MM OR As per customer specification.

SPEED UPTO 160/240 METER PER MINUTE.

#### STANDARD FRAME SIZE OF 12 SPINDLE UNIT:

LENGTH : 152 CM

WIDTH : 76 CM

HEIGHT : 176 CM

POWER REQUIREMENT PER SPINDLE - 0.18 KW

#### MOTOR SPECIFICATIONS:

RPM : 2800

PHASE : III (THREE)

HP : 0.25

V : 400-440 A.C

\* Along with continuous development and improvement in our machine, we reserve the rights to change the design, dimensions and specifications without prior notice.

## Profile

With the mission of exceeding customer needs through the leveraging of skills, technology and achieving functional excellence, the N-TEX Group, since its inception in 1972, has gained prominence as a leading manufacturer of industrial machinery. The Group has always focused on delivering the best of its products and services through defined processes, stringent quality policies and state-of-the-art technologies. And with clear and focused growth plans on the horizon, the N-TEX Group is geared to design product solutions that satisfy the client's requirements to the core.

Under the dynamic leadership of Mr. Hardashbhai Patel, the N-TEX Group has received acclaim not only in India, but abroad as well, with export operations to countries like Nepal, Sri Lanka, Bangladesh, Zambia, Sudan, Tanzania, Ethiopia, Canada, Iraq, Turkey, Nigeria and South Africa.

The N-TEX Group is involved in the manufacturing of:

- Cheese Winder Machine
- Sutli (PP String) Winder Machine
- Circular Looms
- Printing machine
- Bale Press
- Textile Machinery

N-TEX also provides comprehensive solutions to the woven sacks industry.

Regd. & Corp. Office

**N-TEX Group**

4, Panchal Sahakari Udhyognagar,  
Nr. Vadilal Ice Cream Factory, Dudheshwar Road,  
Ahmedabad-380 004. (Guj.) India.

Phone: +91-79-2562 5772, Telefax: +91-79-2562 1048

E-mail: [sales@ntexgroups.com](mailto:sales@ntexgroups.com)

[www.ntexgroups.com](http://www.ntexgroups.com)



## High Speed Cheese Winder

# High Speed Cheese Winder

## MAGNETIC CLUTCH DRIVE:

Unique permanent magnetic clutch drive for Spindle unit, ensuring smooth operations and high speed.

## PRECISION CAM BOX ASSEMBLY:

Fully enclosed dust proof cam box with self lubricating 50 mm diameter cam. Requires no oiling and is almost maintenance free.

## ONE SNAP LOADING UNLOADING:

Cheese bobbin, new lever mechanism for quick loading unloading of bobbins.

## INDIVIDUAL 'DOL' STARTER

For Protection of motors against single phasing and overheating.

## FINE WINDING RATIO ADJUSTER:

To wind tape yarn with side by side fixed width. Ratio adjustment system is not included in this model.

## RIGID QUALITY CONTROLL:

Standard products and original equipments are used in every stage of the manufacturing process.

## AUTOMATIC TENSION DEVICE:

Unique counter weight automatic tension regulation, for perfect and parallel winding.

